



Cables & Adapters





Adapters



Simplify connectivity with Dell adapters,
whether you're at home, in the office or on the go.



Extensive connectivity

Compatible with a broad range of operating systems, and featuring a wide array of ports available, Dell adapters offer seamless connectivity to various devices and accessories.



Reliability

Dell adapters undergo rigorous testing and work seamlessly with Dell systems. Enjoy peace of mind with Dell's renowned warranty and support services.



Thoughtfully designed

Stay productive wherever you are with compact and portable Dell adapters, designed to travel with you.



Multiport Adapters

Dell Pro 7-in-1 USB-C Travel Hub
– DA310



Dell 6-in-1 USB-C Multiport Adapter
– DA305



USB-C to HDMI/ Display Port



Ports	7	6	3	
Downstream USB-C port	USB 3.2 Gen 2 (10Gbps), Display and Power pass-through	USB 3.2 Gen 2 (10Gbps), Display and Power pass-through	USB 3.2, Display and Power pass-through	
USB-A	2 X USB-A 3.2 (10Gbps)	2 X USB-A 3.2 (10Gbps)	-	
Ethernet (LAN)	1 Gbps	1 Gbps	-	
DisplayPort	1.4, 4K@60Hz ¹	1.4, 4K@60Hz ¹	1.4, 4K@60Hz ¹	
HDMI	2.0, 4K@60Hz ²	2.0, 4K@60Hz ²	2.0, 4K@60Hz ²	
VGA	1920x1080 (1080p)	-	-	
Power Pass-Through	Yes, up to 90W ³	Yes, up to 90W ³	Yes, up to 90W ³	
Fast Role Swap Supportability	Yes	Yes	-	
Enterprise Features	PXE Boot, Wake-On-LAN, MAC address	-	-	
OS Support	Windows 10 (64bit) MacOS, Chrome, RHEL, Ubuntu	Windows 10 (64bit) MacOS, Chrome, RHEL, Ubuntu	Windows 10 (64bit) MacOS, Chrome	
Dimensions (Diameter x Height) (mm)	69.8 x 24.5	69.8 x 24.5	65 x 62	
USB-C cable length (mm)	120	120	180	
Weight (g)	80	84	63	

Read More

Read More

¹ Available with select PC models (that support DisplayPort 1.2 and above) and when connected to displays that offer 4K resolution at 60Hz. ² Available with select PC models (that support DisplayPort 1.4 and above) and when connected to displays that offer 4K resolution at 60Hz, with HDR10 support. ³ Up to 90W can pass through the port to charge your USB-C laptop. Actual power supplied is dependent on your power source/ platform power policy. Product availability may vary by country, please refer to the product page on Dell.com for more information.



Dell Single
Function Adapters
(USB-C)

Dell Adapter –
USB-C to HDMI 2.1



Dell Adapter –
USB-C to DP



Dell Adapter –
USB-C to Ethernet (2.5Gbps)



Dell Adapter –
USB-C to USB-A



Color	Black	Black	Black	Black	
Interface	USB-C	USB-C	USB-C	USB-C	
Connector A (Plug into notebook/ desktop)	USB-C (Male)	USB-C (Male)	USB-C (Male)	USB-C (Male)	
Connector B (Interface to devices)	HDMI 2.1 (Female)	DP1.2 (Female)	Ethernet RJ-45 (Female)	USB-A (Female)	
Supported OS	- All Windows - BIOS	- All Windows - BIOS	- All Windows - BIOS	- All Windows - BIOS	
Resolution	4096 x 2160 @ 144Hz	4096 x 2160 @ 60Hz	–	–	



Dell Single
Function Adapters
(Legacy)


Dell Adapter –
DisplayPort to VGA



Dell Adapter –
DisplayPort to HDMI2.0 (4K)



Dell HDMI 2.0 Cable



Dell DisplayPort 1.4 Cable



Dell Adapter –
HDMI to VGA



Dell Adapter –
USB 3.0 to Ethernet



Color	Black	Black	Black	Black	Black	Black
Interface	DisplayPort	DisplayPort	HDMI	DisplayPort	HDMI	USB 3.0
Connector A (Plug into notebook/ desktop)	DisplayPort (Male)	DisplayPort (Male)	HDMI (Male)	DisplayPort (Male)	HDMI (Male)	USB 3.0 A (Male)
Connector B (Interface to devices)	VGA (Female)	HDMI (Female)	HDMI (Male)	DisplayPort (Male)	VGA (Female)	RJ45 (Female)
Supported OS	- All Windows and Linux. - BIOS.	- All Windows and Linux. - BIOS.	- All Windows and Linux. - BIOS.	- All Windows and Linux. - BIOS.	- All Windows and Linux. - BIOS.	- All Windows
Resolution	Up to 1920 x 1200 @ 60Hz	Up to 3840 x 2160 @ 60hz	Up to 4K (3840x160) @60Hz Up to 5K (5120x880) @60Hz with use of 4-2-0 pixel	Up to 5120×2880 @60Hz with HDRUp to 8K (7680×4320)@60Hz with use of 4-2-0 pixel	Up to 1920 x 1080 @ 60Hz	Up to 1Gbps